

NR_key_name: DC7CFDA21AA5C3BF85256659006BE5D5

SendTo: ALL

CopyTo:

DisplayBlindCopyTo:

BlindCopyTo: CN=R ecord/O=ARRB

From: CN=Tracy Shycoff/O=ARRB

DisplayFromDomain:

DisplayDate: 08/07/1998

DisplayDate_Time: 4:37:11 PM

ComposedDate: 08/07/1998

ComposedDate_Time: 3:38:32 PM

Subject: front door

The front door is fixed (hopefully for the last time). I know that some off you will scoff at this but here is how we can keep the door working properly through September 30:DO NOT USE EXCESSIVE FORCE ON THE HANDLE WHEN OPENING THE DOOR. It's as simple as that folks. We apparently are a little too aggressive on our door handle and are bending the inner components of the handle. Please do not push down on the handle as hard as you have perhaps been pushing, and do not continue to push down after the handle stops. Again, I know this sounds silly but we've had a locksmith company out here three times in the last few months. They have taken the door lock mechanism apart and each time we have the same problem. Even after they replaced the problem with new parts we bent them again! Maybe it's the stress, who knows. In any case these instructions should work.Good luck!

Body:

recstat: Record

DeliveryPriority: N

DeliveryReport: B

ReturnReceipt:

Categories: